

**Amendments to the Claims:**

The listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

- 1 (currently amended): A method of driving a liquid crystal display (LCD)  
5 monitor, the LCD monitor comprising:  
an LCD panel for displaying a plurality of pixels arranged in a matrix  
format; and  
a power supply comprising a plurality of power transmission lines for  
carrying a plurality of voltages, the power transmission lines of the  
10 power supply being electrically coupled to a plurality of driving  
units, each driving unit comprising an output buffer and a switch, a  
first end of the switch being selectively connected to either an  
output terminal of the output buffer or an input terminal of the  
output buffer, a second end of the switch being connected to an  
15 output terminal of the driving unit;  
said method comprising:  
disconnecting the first end of the switch from the input terminal of the  
output buffer and connecting the first end of the switch to the output  
terminal of the output buffer for driving an output voltage of the  
20 driving unit toward a voltage transmitted via the power transmission  
line of the power supply; and  
disconnecting the first end of the switch from the output terminal of the  
output buffer and connecting the first end of the switch to the input  
terminal of the output buffer for driving the output voltage of the  
25 driving unit toward an average voltage generated from averaging  
voltages at output terminals of the driving units that are connected  
to the same power transmission line.

2 (original): The method of claim 1 wherein the output buffer further comprises an operational amplifier.

5 3 (original): The method of claim 1 wherein the output buffer further comprises an operational transconductance amplifier.

4 (original): The method of claim 1 wherein the first end of the switch is first connected to the output terminal of the output buffer and then  
10 connected to the input terminal of the output buffer.

5 (original): The method of claim 4 wherein the driving units that are connected to the same voltage transmitted via the corresponding power transmission line of the power supply simultaneously drive the pixels  
15 located in a row of the LCD panel toward a target level after the first end of the switch is connected to the input terminal of the output buffer.

6 (original): The method of claim 1 wherein the voltage transmitted via the power transmission line of the power supply is generated by a voltage  
20 divider.

7 (original): The method of claim 1 wherein the power supply further comprises a plurality of multiplexers each electrically connected to one  
25 of the driving units and the power transmission lines, and the multiplexer is used for selecting a current route connecting the driving unit and one of the power transmission lines.

8 (original): A method of driving a liquid crystal display (LCD) monitor,

the LCD monitor comprising:

an LCD panel for displaying a plurality of pixels arranged in a matrix format;

a power supply comprising a plurality of output terminals for outputting

5 a plurality of voltages, each output terminal of the power supply being selectively, electrically coupled to a driving unit, the driving unit comprising an output buffer, a first switch electrically connected to an output terminal of the output buffer and an output terminal of the driving unit, and a second switch connected to an  
10 output terminal of one driving unit and an output terminal of another driving unit, the output terminal of the output buffer being electrically connected to the output terminal of the driving unit when the first switch is turned on, the output terminal of one driving unit being electrically connected to the output terminal of another  
15 driving unit when the second switch is turned on;

said method comprising:

turning on the first switch for driving an output voltage of the driving unit toward a voltage of the output terminal of the power supply that is connected to the driving unit; and

20 turning on the second switch for driving the output voltage of the driving units toward an average voltage generated from averaging voltages at output terminals of the driving units when the driving units are connected to output terminals of the power supply that provide the same voltage.

25

9 (original): The method of claim 8 wherein the output buffer further comprises an operational amplifier.

10 (original): The method of claim 8 wherein the output buffer further

comprises an operational transconductance amplifier.

11 (original): The method of claim 8 wherein the voltage outputted from the power supply is generated by a voltage divider.

5

12 (original): The method of claim 8, wherein the second switch is turned off in said step of turning on the first switch; and the first switch is turned off in said step of turning on the second switch.

10 13 (original): The method of claim 12, further comprising detecting whether two driving units receive the same voltage from the power supply before said step of turning on the second switch, and if two driving units receive the same voltage proceeding with said step of turning on the second switch.

15

14 (original): The method of claim 8 wherein the second switch is connected to output terminals of two driving units, and the two driving units are prepared to drive corresponding pixels with voltages having the same polarity.

20

15 (original): The method of claim 14 wherein the second switch is connected to output terminals of two adjacent driving units.

25 16 (original): The method of claim 14 wherein the second switch is connected to output terminals of two driving units with at least one another driving unit positioned between the two driving units.

17 (original): The method of claim 8 wherein the LCD monitor further comprises a detecting circuit for comparing two input driving data with

regard to the driving units that are connected to the second switch to determine whether the corresponding second switch is turned on or not.

- 5 18 (original): The method of claim 17 wherein the input driving data comprise a plurality of binary bits, and the detecting circuit is a XOR logic circuit for comparing binary bits.
- 10 19 (original): The method of claim 17 wherein the input driving data comprise a plurality of voltage levels, and the detecting circuit is a comparator for comparing voltage levels.
- 15 20 (original): A driving device for driving a liquid crystal display (LCD) monitor, the LCD monitor comprising an LCD panel for displaying a plurality of pixels arranged in a matrix format, said driving device comprising:
- 20 a power supply comprising a plurality of power transmission lines for carrying a plurality of voltages;
- a plurality of driving units electrically coupled to the power transmission lines of said power supply, each driving unit comprising an output buffer and a switch, a first end of said switch being selectively connected to either an output terminal of said output buffer or an input terminal of said output buffer, a second end of said switch being connected to an output terminal of said driving unit;
- 25 wherein the first end of said switch is first connected to the output terminal of said output buffer for driving an output voltage of the driving unit toward a voltage transmitted via the power transmission line of said power supply, and the first end of said switch is then connected to the input terminal of said output buffer for driving the output voltage of said driving unit toward an average voltage generated

from averaging voltages at output terminals of said driving units that are connected to the same power transmission line.

- 21 (original): A driving device for driving a liquid crystal display (LCD) monitor, the  
5 LCD monitor comprising an LCD panel for displaying a plurality of pixels arranged in a matrix format, said driving device comprising:  
a power supply comprising a plurality of output terminals for outputting a plurality of voltages;  
a plurality of driving units electrically connected to the output terminals  
10 of said power supply, said driving unit comprising:  
an output buffer;  
a first switch connected between an output terminal of said output buffer and an output terminal of said driving unit, the output terminal of said output buffer being electrically connected to  
15 the output terminal of said driving unit when said first switch is turned on; and  
a second switch connected between the output terminal of said driving unit and an output terminal of another driving unit, the output terminal of said driving unit being electrically connected  
20 to the output terminal of another driving unit when said second switch is turned on;  
wherein said first switch is first turned on to drive an output voltage of said driving unit toward a voltage of the output terminal of said power supply that is connected to said driving unit, and said second switch is  
25 then turned on to drive the output voltage of said driving units toward an average voltage generated from averaging voltages at output terminals of said driving units when said driving units are connected to output terminals of said power supply that provide the same voltage.

- 22 (original): A driving device for driving a flat panel display including a plurality of pixels arranged in a matrix format, said driving device comprising:
- a first driving units receiving a first voltage and being provided to drive the pixels of the flat panel display, said first driving unit
- 5 comprising:
- a first output buffer;
- a first switch electrically connected between an output terminal of said first output buffer and an output terminal of said first driving unit;
- 10 a second driving units receiving a second voltage and driving the pixels of the flat panel display, said second driving unit comprising:
- a second output buffer;
- a second switch electrically connected between an output terminal of said second output buffer and an output terminal of said
- 15 second driving unit;
- a third switch electrically connected between the output terminal of said first driving unit and the output terminal of said second driving unit; and
- a detecting circuit for controlling said third switch according to the
- 20 first voltage and the second voltage.
- 23 (original): The driving device of claim 22, said third switch is turned on if the first voltage and the second voltage are substantially the same.
- 25 24 (original): A driving device for driving a flat panel display including a plurality of pixels arranged in a matrix format, said driving device comprising:
- a first driving units receiving a first voltage and being provided to drive the pixels of the flat panel display, the first voltage is provided according to a first input driving data, said first driving unit

comprising:

a first output buffer;

a first switch electrically connected between an output terminal of  
said first output buffer and an output terminal of said first  
driving unit;

a second driving unit receiving a second voltage and driving the pixels  
of the flat panel display, the second voltage is provided according to  
a second input driving data, said second driving unit comprising:

a second output buffer;

a second switch electrically connected between an output terminal  
of said second output buffer and an output terminal of said  
second driving unit;

a third switch electrically connected between the output terminal of  
said first driving unit and the output terminal of said second driving  
unit; and

a detecting circuit for controlling said third switch according to the  
first input driving data and the second input driving data.

25 (original): The driving device of claim 24, said third switch is turned on  
if the first input driving data and the second input driving data are the  
same.

26 (new): A driving device for driving a flat panel display apparatus, said  
driving device comprising:

a first driving unit;

a second driving unit;

a third driving unit, wherein said second driving unit is deposited  
between said first driving unit and said third driving unit;

a fourth driving unit, wherein said third driving unit is deposited



between said second driving unit and said fourth driving unit;  
a first switch coupled between an output terminal of said first driving  
unit and an output terminal of said third driving unit; and  
a second switch coupled between an output terminal of said second  
5 driving unit and an output terminal of said fourth driving unit.

27 (new): The driving device of claim 26, wherein said first driving unit  
further receives a first voltage, said first voltage is provided according  
to a first input driving data,  
10 said third driving unit further receives a third voltage, said third voltage  
is provided according to a third input driving data, and  
said first switch is turned on if said first input driving data and said  
third input driving data are the same.